


Metric cable glands for SSX series

3 cable gland options on 1 backshell



| Cable Clamp - Metric (dimensions in mm) | | | | |
|---|----------------------|----|----|----|
| V (thread size) | Ø S (clamping range) | K | Z | L |
| Reduced M 40 | 15 - 23 | 46 | 10 | 52 |
| Normal M 40 | 19 - 28 | 46 | 10 | 52 |
| Oversized M 40 | 22 - 32 | 46 | 10 | 52 |

Metric thread cable glands allow greater versatility compared to PG or other thread types. On the inline versions of the SSX connectors, in fact, three different versions of M40 cable glands can be fitted, resulting in 15 to 32 mm combined cable clamping range for standard inline SSX connectors.

S2W 2-Way splitter box with Syntax SSX 19 pin connectors



S2WSXCS000S



S2WSXCS000S

S2W with Syntax® SSX 19 pin connectors. On the S2W, the SSX 19 pin connectors can be with silver-plated or gold-plated contacts. Standard and reverse versions are available (standard version in the photo). The reverse version differs from the standard for the position where the input connector is assembled (on the reverse version, the input is inline with one of the outputs).

Silver-plated contacts

1 IN power, 2 x OUT Power, standard, p/n S2WSXCS000S
1 IN power, 2 x OUT Power, reverse, p/n S2WSXCS000R

Gold-plated contacts

1 IN power, 2 x OUT Power, standard, p/n S2WSXCG000S
1 IN power, 2 x OUT Power, reverse, p/n S2WSXCG000R

nb: for the version with safety lacing add "-L" at the end of the p/n