







CONTATTI SVK

CRIMP CONTACTS TYPES AND PART N.

Size	Connector	Plating	Part N.	Gender	Part N.	Gender
16	13/19/25/37/54/85 pin	Silver	SVKP16SFC	Female	SVKP16SMC	Male
						
		Gold	SVKP16GFC	Female	SVKP16GMC	Male
						
18	100/150 pin	Gold	SVKP18GFC	Female	SVKP18GMC	Male
						

SOLDER CONTACTS TYPES AND PART N.

Size	Connector	Plating	Part N.	Gender	Part N.	Gender
16	13/19/25/37/54/85 pin	Gold	SVKP16GFS	Female	SVKP16GMS	Male
						

CONTACTS RATING



Size	Max Current	Rated Current	Max Voltage Drop	Wire section (mm ²)	Wire section AWG
16	22 A	13 A	74 mv	1+1,5	18+16
18	10 A	7,5 A	83 mv	0,15+0,6	26+20

CONNECTORS RATING

Contacts number	Operating voltage	Operating voltage	Test voltage	Min. Flashover
	Vdc	Vac	Vac	Vac
13/19/25/150	250	200	1000	1400
37/54/85/100	700	500	2000	2800

CONTATTI SVS

CRIMP CONTACTS TYPES AND PART N.

Size	Connector	Plating	Part N.	Gender	Part N.	Gender
20	72/101 pin	Gold	SVKP20GFC	Female	SVKP20GMC	Male
						

CONTACTS RATING

Size	Max Current	Rated Current	Max Voltage Drop	Wire section (mm ²)	Wire section AWG
20	7,5 A	7,5 A	83 mv	0,15+0,3	26+22

CONNECTORS RATING

Contacts number	Operating voltage	Operating voltage	Test voltage	Min. Flashover
	Vdc	Vac	Vac	Vac
72/101	250	200	1000	1400

