

CONTACTS DETAILS

CRIMP CONTACTS TYPES AND PART N.

Size	Connector	Plating	Part N.	Gender	Part N.	Gender
16	13/19/25/37/54/85 pin	Silver	SVKP16SFC	Female	SVKP16SMC	Male
		Gold	SVKP16GFC	Female	SVKP16GMC	Male
18	100/150 pin	Gold	SVKP18GFC	Female	SVKP18GMC	Male
20	72/101 pin Audio / Video SV 25/6	Gold	SVKP20GFC	Female	SVKP20GMC	Male
11	SSX 19 pin	Silver	SSXP11SFC	Female	SSXP11SMC	Male
		Gold	SSXP11GFC	Female	SSXP11GMC	Male
12	SPK 4/8 pin for 2,5 mm ²	Silver	SPKP12SFC	Female	SPKP12SMC	Male
		Gold	SPKP12GFC	Female	SPKP12GMC	Male
	SPK 4/8 pin for 4,0 mm ²	Silver	SPKP12SFC4	Female	SPKP12SMC4	Male
		Gold	SPKP12GFC4	Female	SPKP12GMC4	Male
RG59	Audio / Video SV 25/6	Gold	SVKP59CXGFC	Female	SVKP59CXGMC	Male

SOLDER CONTACTS TYPES AND PART N.

Size	Connector	Plating	Part N.	Gender	Part N.	Gender
16	13/19/25/37/54/85 pin	Gold	SVKP16GFS	Female	SVKP16GMS	Male
20	SMA 122/176 pin	Gold	SMAP20GFS	Female	SMAP20GMS	Male
11	SSX 19 pin	Silver	SSXP11SFS	Female	SSXP11SMS	Male
		Gold	SSXP11GFS	Female	SSXP11GMS	Male
12	SPK 4/8 pin	Silver	SPKP12SFS	Female	SPKP12SMS	Male
		Gold	SPKP12GFS	Female	SPKP12GMS	Male

CONTACTS RATING

Size	Max Current	Rated Current	Max Voltage Drop	Wire section (mm ²)	Wire section AWG
12	41 A	23 A	63 mv	2+3	12+14
16	22 A	13 A	74 mv	1+1,5	18+16
18	10 A	7,5 A	83 mv	0,15+0,6	26+20
20	7,5 A	7,5 A	83 mv	0,15+0,3	26+22

CONNECTORS RATING

Contacts number	Operating voltage	Operating voltage	Test voltage	Min. Flashover
	Vdc	Vac	Vac	Vac
13/19/25/150 - 72/101	250	200	1000	1400
37/54/85/100	700	500	2000	2800
4/8	1250	900	2800	3800