


PART NUMBER EXPLANATION

Lug Converters with SPY ComLug and EasiLug contacts - Panel version



Example Part Number

SPY 4 PD E GN 1L 120 MQ



Connector Series

SPY for Lug Series

Maximum Current Rating

4 Up to 480amp (25 to 150mm²)
7 Up to 750amp (185 to 300mm²)

Connector Style

PD Panel Drain
PS Panel Source

Key Composition

E Earth
N Neutral
1 Phase 1
2 Phase 2
3 Phase 3

Insulator Color

GN Green 
BL Blue 
BR Brown 
BK Black 
GY Gray 
RD Red 
YE Yellow 
WH White 

Lug contact type

0L EasiLug without lug terminal
1L EasiLug with lug terminal
8L ComLug L Threaded M12 480amp
9L ComLug XL Threaded M12 750amp (oversized body)

Cable Conductor size for EasiLug terminal

000 Without EasiLug terminal / For ComLug L or XL
120 120 mm² aluminum cable
150 150 mm² aluminum cable
185 185 mm² aluminum cable
240 240 mm² aluminum cable
300 300 mm² aluminium cable

SHELTER Special Versions with backshell

00 Connector body without backshell thread
M0 Backshell without cable gland
MQ Threaded body with backshell and reduced M40 gland Ø 15-23 mm
MP Threaded body with backshell and normal M40 gland Ø 19-28 mm
MR Threaded body with backshell and oversized M40 gland Ø 22-32 mm
MU Threaded body with backshell, M40-M50 adaptor M50 gland Ø 30-38 mm
 (please contact us for more information about the sizes)

Special versions

00 No special version

Compatible accessories, to be ordered separately

SPX-SYLOCK SyntaxLock quick secondary lock release system
SPXTKEY Secondary lock release key

SPXDCS-SC IP53 Protective plastic cap kit for source connectors
SPXD-SC IP53 Protective plastic cap kit for drain connectors
SPXDCS-SC-IP67 IP67 protection cap for source connectors
SPXD-SC-IP67 IP67 protection cap for drain connectors